

STAHL®



5000LRX-20-H

Crane Rating: 25,000 ft. lbs.

Maximum lifting capacity: 5,000 lbs.

Boom Length: 20 ft.

20-FOOT TOTAL BOOM REACH

Fully hydraulic extension boom provides 20-ft. of reach

OPERATOR-FRIENDLY WIRELESS REMOTE CONTROLS

Lightweight, proportional wireless FM radio remote control permits single-handed precision operation of the crane

SMOOTH OPERATION

Self-lubricating Nylatron™ bearing allows for smooth operation of inner and outer booms

SECURE FROM UNAUTHORIZED USE

Remote control unit can be quickly detached and locked away to prevent unauthorized use of the unit

Covered by a
1-Year Limited Warranty



Get the complete Crane and Crane Body package you need from STAHL

LIFTING CAPACITIES* - 5000 SERIES

REACH	RETRACTED BOOM	FIRST HYDRAULIC EXTENSION	SECOND HYDRAULIC EXTENSION
3 - 5 ft.	5,000 lbs.		
6 ft.	4,160 lbs.		
7 ft.	3,570 lbs.		
8 ft.	3,125 lbs.		
9 ft.	2,775 lbs.		
10 ft.	2,500 lbs.		
11 ft.		2,270 lbs.	
12 ft.		2,080 lbs.	
13 ft.		1,920 lbs.	
14 ft.		1,785 lbs.	
15 ft.		1,665 lbs.	
16 ft.			1,560 lbs.
17 ft.			1,480 lbs.
18 ft.			1,385 lbs.
19 ft.			1,315 lbs.
20 ft.			1,250 lbs.

*Double Line is required for 2,500+ lb. loads

SPECIFICATIONS

DESCRIPTION	SPECIFICATION
Base Boom Length	10 ft.
First Hydraulic Extension	5 ft.
Second Hydraulic Extension	5 ft.
Rotation System	370° non-continuous hydraulic on turntable bearing with worm drive and dynamic brake
Remote Control	Lightweight, hand-held, proportional wireless FM radio remote control unit
Winch Cable	100 ft. of 5/16" aircraft cable with latch hook, traveling block and down-haul weight
Winch	Hydraulic planetary gear with brake
Winch Line Speed	60 ft. per minute (single line)
Rotation Speed	1 RPM
Boom Elevation	-5° to +75°
Maximum Line Pull	3,000 lb. single line / 5,000 lb. double line
Weight	950 lbs. (approx.)
Length	11 ft. - 6 in.
Width	20 in.
Height	30 in.
Minimum Chassis Requirements	14,500 GVW
Hydraulic Requirements	Pump output of 8 GPM @ 2750 PSI
Outrigger	Truck must be equipped with heavy-duty outrigger



www.anjerinc.com
800-326-5373
sales@anjerinc.com