

TUCKUNDER™ SERIES

LIFTING CAPACITIES (LBS): 1500, 2000, 2500, 3000



KEY ADVANTAGES

1. HD Mechanical Safety Latch

Redundant-system stowage in addition to hydraulic lock

2. Spring Assist Platform

Dual torsion springs provide effortiess platform operation

3. **EZ Mount**

center mark for easy installation. Floor extension may be bolted to the truck.

4. CHS - Centralized Hydraulic System

All sensitive hydraulic and electrical components housed safely within the stainless steel pump box.

5. Lifetime-Warranty Service Free Bushings
Used at all critical pivot points to reduce wear wi

Used at all critical pivot points to reduce wear without the need for routine lubrication.

STANDARD FEATURES

- Circuit Protection

200 Amp fuse protects truck wiring from a "dead short".

- Marine Duty Potted Toggle Switch

Heavy duty toggle, potted to permanently separate and seal electrical connections from corrosion.

- 3/16" Steel Floor Extension

Rugged and attractive surface.

- Industry-Leading Warranty

2 years mechanical + 2 years electrical & hydraulic, parts and labor.

- Pressure Compensated Flow Valve

Constant, controlled speeds at all times. Prevents "free-fall" under certain hydraulic failures.

- Anthony 3-Step Powder Coat

Steel components are washed, shot blast prepped, and coated with premium finish.

- Max Duty Dock Bumpers

Helps protect floor extension from contact with dock. Includes rubber bumpers.

QUALITY COMES STANDARD

AVAILABLE MODELS, PLATFORMS AND CAPACITIES

Model	AST-1500	AST-2000	AST-2500	AST-3000	AST-3500	
Capacity (lbs)	1500	2000	2500	3000	3500	
Bed Height Range			42" - 57"			
Available Platforms						
Steel or Aluminum 80" x 38" + 5" Ramped						
Steel or Aluminum 80" x 45" + 6" Ramped						
Steel or Aluminum 80" x 50" Wedge*						
Steel or Aluminum 80" x 48" + 12" ARR						


ASTL-1800	ASTL-2500				
1800	2500				
36" - 44"					
Available Platforms					
Steel 80" x 44" Wedge (standard)					
Aluminum 80" x 44" Wedge					
	1800 36" - 44' Available Platforms 0" x 44" Wedge (standard)				

^{*}Cart stops available. 39" load area when deployed.

OPTIONS

- Cart stops
- Power down
- Alternate floor extensions: 3/16", 1/4", or 3/8" steel. 96" or 102" Wide
- Wireless, removable handheld corded, flush mount, or dual control options.
- Stainless steel toggle switch guard
- Third step add-on for dock bumper
- Galvanized finish with extended warranty
- ICC bumper
- Cab or ignition cutoff switch
- 5 & 12 ton pintle hook / ball hitch brackets
- Walkramp capability
- Battery box

TRUCK MOUNTING REQUIREMENTS





www.anjerinc.com 800-326-5373 sales@anjerinc.com